

Gate Burton Energy Park

Preliminary Environmental Information Report

Volume 3, Appendix 11-B: Acoustic Terminology

June 2022

Gate Burton Energy Park Limited

Quality information

Prepared by

ER

Checked by

YL

Verified by

YL

Approved by

YL

Prepared for:

Gate Burton Energy Park Limited

Prepared by:

AECOM Limited

© 2022 AECOM Limited. All Rights Reserved.

This document has been prepared by AECOM Limited (“AECOM”) for sole use of our client (the “Client”) in accordance with generally accepted consultancy principles, the budget for fees and the terms of reference agreed between AECOM and the Client. Any information provided by third parties and referred to herein has not been checked or verified by AECOM, unless otherwise expressly stated in the document. No third party may rely upon this document without the prior and express written agreement of AECOM.



Table of Contents

| | | |
|----|----------------------------|---|
| 1. | Acoustic Terminology | 1 |
|----|----------------------------|---|

1. Acoustic Terminology

1.1.1 Acoustic terminology used in the noise and vibration assessment are summarised in Table 11-1.

Table 11-1 Acoustic Terminology

| Term | Description |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Noise | Unwanted or unexpected sound. |
| Frequency (Hz) | The number of cycles per second (i.e., the number of vibrations that occur in one second); subjectively this is perceived as pitch. |
| Frequency Spectrum | The relative frequency contributions that make up a noise. |
| "A" Weighting (dB(A)) | The human ear does not respond uniformly across the audible frequency range. The "A" weighting is commonly used to simulate the frequency response of the ear. |
| Decibel (dB) | The decibel is a logarithmic ratio of two values of a variable. The range of audible sound pressures is approximately 2×10^{-5} Pa to 200 Pa. Using decibel notation presents this range in a more manageable form, 0 dB to 140 dB. |
| Sound Pressure Level (Lp) | Equal to 20 times the logarithm to the base 10 of the ratio of the root mean squared (RMS) sound pressure to the reference sound pressure. In air the reference sound pressure is 2×10^{-5} Pa. Mathematically: $\text{Sound Pressure Level (dB)} = 20 \log_{10} \{p(t) / P_0\}$ Where $P_0 = 2 \times 10^{-5}$ Pa |
| Ambient Noise Level, LAeq,T | The equivalent continuous A-weighted sound pressure level of the totally encompassing sound in a given situation at a given time that is usually composed of sound from many sources near and far. |
| Background Noise Level LA90,T | The A-weighted sound pressure level of the residual noise at the assessment position that is exceeded for 90% of a given time interval, T, measured using the fast time weighting, F, and quoted to the nearest whole number. |
| Reference Time Interval, Tr | The specified interval over which an equivalent continuous A-weighted sound pressure level is determined. |
| Specific Noise Level, LAeq,Tr | The equivalent continuous A-weighted sound pressure level at the assessment position produced by the specific noise source over a given reference time interval. |
| Rating Level, LAr,Tr | The specific noise level plus any adjustment for any characteristic features of the noise. |
| Level LA10,T | The A-weighted sound pressure level exceeded for 10% of a given time interval, T, measured using the fast time weighting, F. |
| Noise | Unwanted or unexpected sound. |
| Frequency (Hz) | The number of cycles per second (i.e., the number of vibrations that occur in one second); subjectively this is perceived as pitch. |

| Term | Description |
|--------------------|------------------------------------------------------------|
| Frequency Spectrum | The relative frequency contributions that make up a noise. |

1.1.2 Between the quietest audible sound and the loudest tolerable sound, there is a ten million to one ratio in sound pressure (measured in pascals, Pa). Because of this wide range, a noise level scale based on logarithms is used in noise measurement called the decibel (dB) scale. Audibility of sound covers a range of approximately 0 to 140 dB.

Table 11-2 Sound Pressure Level in dB LpA for Common Situations

| Typical Noise Level, dB LpA | Example |
|-----------------------------|------------------------------------------------------------------------|
| 0 | Threshold of hearing |
| 30 | Rural area at night, still air |
| 40 | Public library Refrigerator humming at 2 m |
| 50 | Quiet office, no machinery Boiling kettle at 0.5 m |
| 60 | Normal conversation |
| 70 | Telephone ringing at 2 m Vacuum cleaner at 3 m |
| 80 | General factory noise level |
| 90 | Heavy goods vehicle from pavement Powered lawnmower, operator's ear |
| 100 | Pneumatic drill at 5 m |
| 120 | Discotheque – 1 m in front of loudspeaker |